



Approvals



## Part Number/Price

| Part #        | Description                                                 | Est. Weight | Price   |
|---------------|-------------------------------------------------------------|-------------|---------|
| 167516        | DT4xW 4 in direct thermal, 110/240 VAC printer              | 3.3 lb      | Consult |
| 167628        | Label peeler, black                                         | —           | Consult |
| 167629        | Cutter, black                                               | —           | Consult |
| 150743        | Printhead                                                   | —           | Consult |
| 107638        | Guardian enclosure                                          | —           | Consult |
| <b>Cables</b> |                                                             |             |         |
| 41276         | 6 ft serial cable DB9 M to blunt end (Rice Lake indicators) | —           | Consult |
| 79074         | USB-A (male) to USB-B (male) cable, 6 ft                    | —           | Consult |
| 64661         | 6 ft serial cable DB9 M to 8-Pin DIN                        | —           | Consult |
| 64660         | 6 ft serial cable DB9 M to DB9 male                         | —           | Consult |
| Consult       | Custom RS-232 serial cable                                  | —           | Consult |

## Options/Accessories

| Part #                    | Description                                                          | Price        |
|---------------------------|----------------------------------------------------------------------|--------------|
| 38941                     | Cleaning pen for open printhead printers 12/box                      | Consult      |
| 35664                     | Cleaning cards, (W × L) 4x 6 in for RL-42DT and RL-42TT              | Consult      |
| 111085                    | Power supply, printers                                               | Consult      |
| 15438                     | Power cord, detachable                                               | Consult      |
| 193466                    | Real-time clock for DT4xW                                            | Consult      |
| <b>Label Stock/Ribbon</b> |                                                                      |              |
| 53251                     | Direct thermal, (W × L) 4 × 3 in, 5 in diameter with perf., 930/roll | Consult/roll |
| 40331                     | Direct thermal, (W × L) 4 × 4 in, 5 in diameter with perf., 745/roll | Consult/roll |
| 37345                     | Direct thermal, (W × L) 4 × 6 in, 5 in diameter with perf., 450/roll | Consult/roll |

## Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL or Q-Label
- 203 dpi (8 dot/mm)
- Drop-in media loading
- USB, Ethernet and RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection
- Direct thermal
- 32-bit CPU

## Specifications

## Print Speed:

Up to 7 ips

## Print Length:

Minimum: 0.16 in

Maximum: 68 in

## Print Width:

4.25 in

## Media:

Continuous form, gap labeling, black mark sensing and punched sensing  
Label roll OD max: 5.0 in

## Core:

1 in, 1.5 in

Thickness: 0.06 mm to 0.20 mm

## Printer Language:

GZPL or GEPL, EZ PL auto switch

## Resident Fonts:

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically. All bit mapped fonts in eight orientations

## Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C,) UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5,) 2 of 5, EAN 8/13 (add on 2 and 5.) Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

## Interfaces:

Baud rate 4800 to 115,200;  
USB port U2.0 (B-type)  
Ethernet (RJ-45)  
RS-232 (DB-9F)

## Power:

Auto switching 100/240 VAC 50/60 Hz

## Memory:

8 MB flash

## Temperature Range:

Operation: 41 °F to 104 °F

(5 °C to 40 °C)

Storage: -4 °F to 122 °F

(-20 °C to 50 °C)

## Humidity:

Operation: 30 to 85% non-condensing, free air

Storage: 10 to 90% non-condensing, free air

## Dimensions:

(L × W × H)

8.58 × 6.53 × 6.61 in

(218 × 166 × 168 mm)

## Weight:

3.3 lb

## Approvals:

CE (EMC), FCC Class A, CB, CUL, CCC

## Warranty:

Two-year limited