

RICE LAKE, Captured Ball Floor Scale Leveling Feet.

Standard Features

Carbon Steel

- Bright zinc and clear chromate plating for corrosion-resistance
- Active ball suspension provides ideal load cell loading with maximum side load protection
- Hardened alloy steel with plated finish
- Includes two jam nuts, one for wrench access
- Top of stud is machined undersize 10% for easy alignment into load cell plus slotted for top-access applications



Carbon

Stainless Steel

- Provides outstanding accuracy, repeatability and performance
- Active ball suspension provides optimum load cell performance
- Hardened stainless steel material, welded, with polished finish
- Includes two stainless steel jam nuts, one for wrench access
- Top of stud is machined undersize 10% for easy alignment into load cell plus slotted for top-access applications



Stainless Steel

Part Number/Price

PART #	FOOT DIA	THREAD SIZE INCHES
Carbon Steel		
74578	1.87 in	1/2-20 UNF
74579	2.00 in	1/2-20 UNF
74580	2.50 in	1/2-20 UNF
74581	3.00 in	1/2-20 UNF
74582	3.00 in	3/4-16 UNF
74583	3.00 in	1-12 UNF
74584	3.00 in	1-14 UNF
171449	3.00 in	1-14 UNF
173018	4.40 in	3/4-16 UNF
174937	5.40 in	3/16 UNF
Stainless Steel		
74572	1.87 in	1/2-20 UNF
74573	2.00 in	1/2-20 UNF
73800	2.50 in	1/2-20 UNF
74574	3.00 in	1/2-20 UNF
74575	3.00 in	3/4-16 UNF
74576	3.00 in	1-12 UNF
74577	3.00 in	1-14 UNF
92380*	2.50 in	1/2-20 UNF
175615	3.47 in	1/2-20NF

*Stem is fully threaded