

### Standard Features

- External weight calibration
- Seven-segment (main)/ 16-segment (sub) display
- Selectable modes: Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal and Formulation
- Mono-metal tuning fork technology (MMTF) provides quick response and stability
- 30-step bar graph display
- AA dry-cell port, (150 hours continuous use with LCD backlight and communication signal ON)
- RS-232 interface for connecting to printer or PC
- Glass breeze break (TE-223, TE-322NC and TE-623 only)

### Specifications

#### Weighing Units:

Milligram, Gram, Ounce, Pound, Carat, Pennyweight, Troy Ounce (see technical manual for complete listing)

#### Operating Modes:

Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal, Formulation

#### Power:

100 to 240 V AC adapter, AA dry cell (batteries not included)

#### Operating Temperature:

41 °F to 95 °F (5 °C to 35 °C)

#### Est. Weight:

TE-223 / 322NC: 6.5 lb (3 kg)  
 TE-623 / 3202 / 6202 / 15001 / 1501NC / 8200NC:  
 6.0 lb (2.7 kg)

#### Warranty:

Five-year limited

#### Return Policy:

Rice Lake standard policy

#### Approvals:

NTEP Certified CC 17-104  
 Measurement Canada AM-6169



| Model                                                 | Capacity | Resolution | NTEP Resolution | Pan Size                    | Weighing Chamber               | Dimensions                                | Part #        | List Price |
|-------------------------------------------------------|----------|------------|-----------------|-----------------------------|--------------------------------|-------------------------------------------|---------------|------------|
| <b>NTEP Certified Only</b>                            |          |            |                 |                             |                                |                                           |               |            |
| <b>TE-223</b>                                         | 220 g    | 0.001 g    | 0.01 g          | 4.6 in (118 mm)             | 226 mm H x 150 mm W x 150 mm D | 10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm) | <b>187600</b> | Consult    |
| <b>TE-623</b>                                         | 620 g    | 0.001 g    | 0.01 g          | 4.6 in (118 mm)             | N/A                            | 10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm) | <b>186030</b> | Consult    |
| <b>TE-3202</b>                                        | 3,200 g  | 0.01 g     | 0.1 g           | 6.3 x 7.1 in (160 x 180 mm) | N/A                            | 10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)   | <b>186035</b> | Consult    |
| <b>TE-6202</b>                                        | 6,200 g  | 0.01 g     | 0.1 g           | 6.3 x 7.1 in (160 x 180 mm) | N/A                            | 10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)   | <b>186036</b> | Consult    |
| <b>TE-15001</b>                                       | 15,000 g | 0.1 g      | 1.0 g           | 6.3 x 7.1 in (160 x 180 mm) | N/A                            | 10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)   | <b>186037</b> | Consult    |
| <b>NTEP Certified and Measurement Canada Approved</b> |          |            |                 |                             |                                |                                           |               |            |
| <b>TE-322NC</b>                                       | 320 g    | 0.01 g     | 0.01 g          | 4.6 in (118 mm)             | 226 mm H x 150 mm W x 150mm D  | 10.6 x 8.1 x 11.8 in (270 x 208 x 301 mm) | <b>204688</b> | Consult    |
| <b>TE-1501NC</b>                                      | 1,500 g  | 0.1 g      | 0.1 g           | 6.3 x 7.1 in (160 x 180 mm) | N/A                            | 10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)   | <b>204689</b> | Consult    |
| <b>TE-8200NC</b>                                      | 8,200 g  | 1 g        | 1 g             | 6.3 x 7.1 in (160 x 180 mm) | N/A                            | 10.4 x 7.5 x 3.4 in (265 x 192 x 86 mm)   | <b>204690</b> | Consult    |

### Options/Accessories

| Part#         | Description                                 | Price   |
|---------------|---------------------------------------------|---------|
| <b>186074</b> | Power supply 100-240 VAC, 50-60 Hz          | Consult |
| <b>186075</b> | In-use dust cover 620 g models and lower    | Consult |
| <b>186076</b> | In-use dust cover 3,200 g models and higher | Consult |
| <b>186077</b> | Specific Density Measurement Kit            | Consult |
| <b>186079</b> | Ethernet TCP/IP option card                 | Consult |

