

OHAUS® Ranger™ Count 3000

Industrial Counting Scales

Solo Basculas

SOLUCIONES DE PESO



Approvals



Part Number/Price

Part #	Model #	Description (lb) (kg) (oz) (g)	Est. Weight	Price
157273	RC31P1502	3 × 0.0001 lb (1.5 × 0.00005 kg) (48 × 0.002 oz) (1,500 × 0.05 g)	12 lb (5.45 kg)	Consult
157275	RC31P3	6 × 0.0002 lb (3 × 0.0001 kg) (96 × 0.05 oz) (3,000 × 0.1 g)	12 lb (5.45 kg)	Consult
157277	RC31P6	15 × 0.0005 lb (6 × 0.0002 kg) (240 × 0.01 oz) (6,000 × 0.2 g)	12 lb (5.45 kg)	Consult
157278	RC31P15	30 × 0.001 lb (15 × 0.0005 kg) (480 × 0.02 oz) (15,000 × 0.5 g)	12 lb (5.45 kg)	Consult
157279	RC31P30	60 × 0.002 lb (30 × 0.001 kg) (960 × 0.05 oz) (30,000 × 1 g)	12 lb (5.45 kg)	Consult

Options/Accessories

Part #	Description	Price
157280	Remote second scale option kit	Consult
154638	Ethernet kit	Consult

Standard Features

- Weigh in kilograms, pounds, grams or ounces
- 30-item data storage
- Three backlit LCD display windows
- RS-232 output
- Quick stabilization

Options

- Ethernet
- Remote scale

Specifications

Internal Resolution:

1/500,000

Display:

Seven-segment 1/30,000, six-digit

Power Source (included):

100 to 240 VAC, 50 to 60 Hz internal universal power supply

Battery:

Lead acid, 210 hours, 12 hours recharge

Number of Scale Channels:

One local
One remote (optional)

Memory Items:

(30)12-digit part number, average piece weights, check counting or checkweighing parameters, tare weights, accumulated weights or counts

Operating Temperature:

14 °F to 104 °F (-10 °C to 40 °C)

Dimensions:

(L × W × H)
12.2 × 12.9 × 4.6 in
(311 × 327 × 117 mm)

Platter Size:

11.8 × 8.9 in (300 × 225 mm)

Approvals:

NTEP Certified 13-022 3000 e
CAN/CSA-C22.2 No. 61010-1-04
UL Std. No. 61010-1 (2nd edition)

Warranty:

One-year limited