



## Specifications

### Capacity (Dual Range):

0 to 15 x 0.005 lb, 15 to 30 x 0.01 lb

### Print Speed:

3.9/ 4.7/ 5.9 in/sec  
(100/ 120/ 150 mm/sec)

### Label Size:

Width: 1.2 to 3.1 in (30 to 80 mm)  
Length: 0.8 to 7.9 in (20 to 200 mm)

### Display:

Operator side: 12 in (800 x 600)  
color touch panel  
Uni-9DB: 8.4 in  
Customer side: 7 in (800 x 480)  
or 12 in (800 x 600) for bench,  
12 in for other models  
Type: Five-wire resistive

### Display Items:

Tare: Four-digits  
Unit price: Six-digits  
Weight: Five-digits  
Total price: Six-digits

### Memory:

SSD memory 250 MB

### Communications:

Static TCP/IP 1G Base T Ethernet  
(auto-duplex) Wireless WEP/WPA/WPA2

### Input/Output:

LAN 1 channel  
USB 4 channel  
SD 1 channel (SDHC: MAX 32 GB)  
(for transaction data)

### Operating Voltage:

Range: 100 to 240 V, 50/60 Hz  
Permissible Tolerance: +/- 10%

### Operating Environment:

32 °F to 104°F (0°C to 40°C)  
20 to 85% relative humidity

### Power Supply:

AC100 to 240 V, 50/60 Hz

### Power Consumption:

Stand-by: 50 W  
In operation: 120 W

### Classification:

NTEP CC 12-121  
UL listed

### Warranty:

One-year limited



## Ishida Uni-9

PC-based, Price Computing Scale/Printer/Color Touchscreen

Uni-9's compact design fits nicely on virtually any size counter, occupying a very small footprint. This PC-based scale is available with a 7- or 12-inch LED backlit customer display for stunning promotional images and videos. The PC-based technology together with a crystal-sharp LED display, provide more marketing capabilities such as video with sound and product pairing promotions. In addition, more behind-the-counter functions such as store intranet access through a browser, recipe lookup, order entry and training videos reduce the need for additional PCs in all departments.

Available with or without a seven-inch customer display, the Uni-9 Series bench scale is ideal for both backroom production and the countertop.

## Standard Features

- Large color touchscreen (12 in)
- Adjustable touchscreen viewing angle
- Customer display can play video on either 12.1 in (800 x 600) or 7 in (800 x 480) screen, bench scale only
- Dual-range weighing (0 to 15 lb x 0.005 lb, 15 to 30 lb x 0.01 lb)
- Label printing: die-cut labels and/or continuous paper
- Customizable label formats: 999
- Up to seven label cassettes allow quick label changing or easy switching to different size labels
- Intranet browsing capabilities for order entry, recipe lookup and more
- PC-based scale operating system
- Solid state drive eliminates moving parts
- SD memory card slot
- SSD memory 250 MB
- 80 mm wide printing
- Up to 150 mm/sec print speed
- 2020 nutrition labeling
- Configurable for different languages including Spanish, French and German
- Fully compliant with RoHS regulations for a completely lead-free machine
- Barcodes: EAN/UPC 8/12/13, ITF FS1, QR CODE, Databar/Limited/Expanded, CODE128, EAN128
- Compatible with third-party communication software, including ADC's InterScale, Invatron's PLUM and Droste's PCScale Manager

PART #	MODEL	WIRELESS	CAPACITY
211871	Uni-9 Bench	√	0-15 x 0.005 lb/15-30 x 0.01 lb
170095	Uni-9 Bench Linerless	√	0-15 x 0.005 lb/15-30 x 0.01 lb
168873	Uni-9D Bench		0-15 x 0.005 lb/15-30 x 0.01 lb
151251	Uni-9 Short Pole	√	0-15 x 0.005 lb/15-30 x 0.01 lb
170096	Uni-9 Pole	√	0-15 x 0.005 lb/15-30 x 0.01 lb
LABELER			
160262	Uni-9 Bench	√	N/A



Bench model customer display



Short Pole model customer display



Bench model with label  
(pictured with platter 171675)



DB bench model