



## Ishida Uni-5

Price Computing Scale/Printer/Color Touchscreen

The Uni-5 Series packs many features into an attractive low profile, small footprint case. The seven-inch color touch panel is easy to master. The operator display consists of windows for tare, weight, unit price and total price.

The membrane keyboard contains standard function keys and can be customized to include PLU, tare, and category presets plus a large number of specialized functions. Icons identify connectivity status, printing mode, and USB port. The programmable color touchscreen can be configured with three key sizes and up to 20 presets per page.

Operators can view virtual receipts, open tickets and totals before printing. The bright grayscale customer display can scroll and flash advertising messages and images. The fast and easy side-loading direct thermal printer has a variable speed and backing re-winder to quickly switch between labels and receipts.

The Ishida Uni-5 Series includes Ethernet (100Mbps) for connection to PC and other scales.

### Specifications

#### Capacity (Dual Range):

0 to 15 × 0.005 lb, 15 to 30 × 0.01 lb

#### Capacity (Single Range):

60 × 0.02 lb option

#### Display:

Operator: Color LCD, 7 in

Customer: Grayscale LCD, 7 in

#### Display Items:

Tare: Four-digits

Unit price: Six-digits

Weight: Five-digits

Total price: Six-digits

#### Preset Keys:

1980: 20 × 99 pages

#### Memory Capacity:

4 MB

#### Communications:

Static TCP/IP 10/100 Base T Ethernet

Wireless WEP/WPA/WPA2

#### Interface:

USB port, back-up and restore only

#### Platter:

15.7 × 10.8 in (398 × 275 mm)

#### Print Head:

Direct thermal 2.2 in head (56 mm)

#### Print Speed:

3.2/ 3.9/ 4.7/ 5.9 in/sec  
(80/ 100/ 120/ 150 mm/sec)

#### Label Size:

Width: 1.5 to 2.5 in (38 to 64 mm)  
Length: 1.5 to 7.9 in (38 to 200 mm)

#### Label Roll:

Inside diameter: 1.6 in (40 mm) min

Outside diameter: 3.9 in (100 mm) max

#### Label Backing Paper:

Width: Up to 2.6 in (66 mm)

#### Power Supply:

AC 100 to 240 V, 50/60 Hz

#### Power Consumption:

Stand-by: 50 W

In operation: 120 W

#### Classification:

NTEP CC 07-099

UL listed

#### Warranty:

One-year limited



### Standard Features

- Large color touchscreen (7 in)
- Dual-range weighing (0 to 15 lb × 0.005 lb/ 15 to 30 lb × 0.01 lb)
- Ethernet communications
- Up to 99 pages of preset keys
- Adjustable touchscreen viewing angle
- 77 tactile keys
- 4 MB memory
- Grayscale LCD customer-side display
- Self-serve mode/operation
- 30+ selectable fixed bar code formats
- 2020 nutrition labeling
- Configurable for different languages including Spanish, French and German
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

| PART # | MODEL       | WIRELESS | CAPACITY                        |
|--------|-------------|----------|---------------------------------|
| 119359 | Uni-5 Bench |          | 0-15 x 0.005 lb/15-30 x 0.01 lb |
| 119356 | Uni-5 Bench | √        | 0-15 x 0.005 lb/15-30 x 0.01 lb |
| 119360 | Uni-5 Pole  |          | 0-15 x 0.005 lb/15-30 x 0.01 lb |
| 119357 | Uni-5 Pole  | √        | 0-15 x 0.005 lb/15-30 x 0.01 lb |
| 154737 | Uni-5 Bench |          | 0-60 x 0.02 lb                  |
| 155264 | Uni-5 Bench | √        | 0-60 x 0.02 lb                  |
| 155265 | Uni-5 Pole  | √        | 0-60 x 0.02 lb                  |



Side-loading printer



Pole scale customer side