



Ishida Uni-7

Price Computing Scale/Printer/Color Touchscreen

The Uni-7 line offers its own set of unique features. Starting with the color touchscreen, users can also customize the customer display with their own color photos.

Save space and time with a front-loading label cassette. The Uni-7 also operates in receipt mode and can drive a cash drawer for basic register and scale operations.

Standard Features

- Large color touchscreen (7 in)
- Adjustable touchscreen viewing angle
- Color graphics on customer-side display (not available on part number 109368, labeler scale)
- Dual-range weighing (0 to 15 lb \times 0.005 lb/ 15 to 30 lb \times 0.01 lb)
- Front-load label cassette
- Supports multiple label formats
- Ethernet communications
- Up to 99 pages of preset keys
- 77 tactile keys
- 4 MB standard memory expandable to 2 GB
- Self-serve mode/operation
- 30+ selectable fixed bar code formats
- Configurable for different languages including Spanish, French and German
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale
- 2020 nutrition labeling

Specifications

Capacity (Dual Range):

0 to 15 \times 0.005 lb, 15 to 30 \times 0.01 lb

Capacity (Single Range):

0.60 \times 0.02 lb option

Display:

Operator: Color LCD, 7 in
Customer: Color LCD, 7 in

Display Items:

Tare: Four-digits
Unit price: Six-digits
Weight: Five-digits
Total price: Six-digits

Preset Keys:

1980: 20 \times 99 pages

Memory Capacity:

4 MB expandable to 2 GB

Communications:

Static TCP/IP 10/100 Base T Ethernet
Wireless WEP/WPA/WPA2

Interface:

USB port (backup and restore only)

Platter:

15.7 \times 10.8 in (398 \times 275 mm)

Print Head:

Direct thermal 2.2 in head (56 mm)

Print Speed:

3.2/ 3.9/ 4.7/ 5.9 in/sec
(80/ 100/ 120/ 150 mm/sec)

Label Size:

Width: 1.2 to 2.5 in (30 to 64 mm)
Length: 0.8 to 7.9 in (20 to 200 mm)

Label Roll:

Inside diameter: 1.6 in (40 mm) min
Outside diameter: 3.9 in (100 mm) max

Label Backing Paper:

Width: Up to 2.6 in (66 mm)

Power Supply:

AC100 to 240 V, 50/60 Hz

Power Consumption:

Stand-by: 50 W
In operation: 120 W

Classification:

NTEP CC 07-099
UL listed

Warranty:

One-year limited



PART #	MODEL	WIRELESS	CAPACITY
161937	Uni-7 Bench		0-15 \times 0.005 lb/15-30 \times 0.01 lb
109366	Uni-7 Bench	√	0-15 \times 0.005 lb/15-30 \times 0.01 lb
166268	Uni-7 Pole		0-15 \times 0.005 lb/15-30 \times 0.01 lb
109367	Uni-7 Pole	√	0-15 \times 0.005 lb/15-30 \times 0.01 lb
155266	Uni-7 Bench	√	0-60 \times 0.02 lb
155267	Uni-7 Pole	√	0-60 \times 0.02 lb
LABELER			
109368	Uni-7 Bench	√	N/A



Self-serve Large Button



Label cassette



Fish Platter