

SURVIVOR® PT-M

Levertronic, Concrete Deck

Solo Basculas

SOLUCIONES DE PESO



Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Steel weighbridge; lever system; inboard transverse lever (for electronic conversion) is furnished unless outboard lever is specified at time of order; standard paint system is a high-performance epoxy base coat.

Package does not include:

Foundation rebar; corrugated sheeting; pit angle coping; deck rebar; bumper plates; foundation bolts; assembly bolts; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- In-pit foundation
- Ideal for limited access locations
- Structural steel pipe lever system
- NTEP Certified 05-018
- Standard levers: 32.5 ton sectional rating
- Capacities to 400,000 lb
- Standard widths from 10 to 14 ft
- Standard profile 44.5 in

Options

- Load cell stand
- Steel deck
- Pit angle coping
- Deck rebar
- Deck channel
- Bumper plates
- Foundation bolts
- Manhole frames and covers
- Conversion s-beam load cell(s)
- Load cell mounting hardware
- Indicator
- Printer
- Other peripheral equipment

Specifications

Full Scale Capacity:

Standard 60,000 to 200,000 lb
Custom up to 400,000 lb

Concentrated Load Capacity (CLC):

Standard 50,000 to 70,000 lb
Custom up to 100,000 lb

Warranty:

Pivots, bearings, suspension and mounting parts of the corner assemblies: One-year
Weighbridge: Two-year

Approvals:

NTEP Certified 05-018 per H-44, Class IIIL
Measurement Canada AM-5598