

SURVIVOR® ATV-M

Self-Contained Levertronic, Steel Deck

Solo Basculas
SOLUCIONES DE PESO



Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Factory-assembled scale module(s) including weighbridge, deck, lever system installed in scale frame; inboard transverse lever (for electronic conversion) is supplied standard unless outboard transverse lever is specified at time of order; manhole access provided through scale deck; standard paint system is a high-performance epoxy primer on all steel with a top coat of alkyd enamel applied to the exterior surface steel.

Package does not include:

Foundation steel; approach coping angle; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- Above-ground or in-pit foundation
- Factory-assembled, self-contained modules
- Individual module lengths from 10 ft to 40 ft
- Multiple modules create desired scale length
- Standard levers: 32.5 ton sectional rating
- Standard height: 30 in
- NTEP Certified 05-018
- Standard deck: 3/8 in thick diamond safety treadplate
- Standard widths from 10 ft to 14 ft
- Capacities to 400,000 lb

Options

- Side pipe rails
- Steel bulkheads
- Conversion s-beam load cell(s)
- Load cell mounting hardware
- Indicator
- Printer
- Other peripheral equipment

Specifications

Full Scale Capacity:

Standard 60,000 to 200,000 lb
Custom up to 400,000 lb

Concentrated Load Capacity (CLC):

Standard 50,000 to 70,000 lb
Custom up to 100,000 lb

Approvals:

NTEP Certified 05-018 per H-44, Class IIII
Measurement Canada AM-5598

Warranty:

One-year warranty on pivots, bearings, suspension, and mounting parts of the corner assemblies
Two-year warranty on weighbridge