

EPSON, TM-U295 Ticket Printer, 115/230 VAC with RS-232 and power supply,

**Print Speed:**

1.9 to 2.3 lines per second (5 x 7 character, 3 dot line spacing)

**Column Capacity:**

35/42 columns

**Characters Per Line:**

35 standard font

**Print Area:**

2.59 in W (65.8 mm W)

**Character Formation:**

5 x 7 and 7 x 7 dot matrix

**Character Height:**

0.11 standard font

**Character Set:**

Full 96-character ASCII; with software control,  
32 international characters,  
128 x 2 graphic characters

**Line Spacing:**

0.16 in (4.06 mm) software programmable in 1/60 in units

**Print Head Life:**

Approximately 100 million strokes/pin

**Form Thickness:**

Single-ply: 0.003 in to 0.009 in (0.08 mm to 0.23 mm)  
Copy paper: 0.003 in to 0.014 in (0.08 mm to 0.36 mm)

**Ribbon:**

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

**Serial Interfaces:**

RS-232 compatible (25-Pin D-sub)

**Baud Rates:**

1200, 2400, 4800, 9600, selectable

**Parity:**

7 or 8 bits, none, even or odd

**Stop Bits:**

1 or more

**Handshaking:**

DTR/DSR or XON/XOFF control selectable

**Overall Dimensions:**

(W x D x H): 7.08 x 7.49 x 3.99 in (180 x 190.5 x 101.5 mm)

**Approvals:**

UL listed, CSA certified, CE marked

**Warranty:**

One-year limited warranty (includes print head)



**APPROVALS**



**Standard Features**

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to 4-part multicopy ticket printing
- Functions in slave capacity, printing information sent via RS-232
- Uses M66 mechanism

**Part Number/Price**

PART #	DESCRIPTION
23113	TM-U295 Ticket Printer, RS-232, 115/230 VAC with power supply, cool white
35891	TM-U295 Ticket Printer, 115/230 VAC with RS-232 and power supply, 25 DB to blunt end cable, cool white
33816	TM-U295 Ticket Printer, RS-232, 24 VDC, cool white

**Options/Accessories**

PART #	DESCRIPTION
29582	Protective dust cover
29584	Ink cartridge (purple) ERC-27
29583	Ink cartridge (black) ERC-27B
23112	Power supply
34344	Additional operating manual
72309	Power supply, 12 VDC vehicle cigarette plug
<b>Cables</b>	
15568	25-Pin D-sub male to 25-Pin D-sub male RS-232 serial interface cable
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface cable (Rice Lake indicators)
41279	25-Pin D-sub male to 9-Pin D-sub male, RS-232 with handshaking
32810	25-Pin D-sub male to 8-Pin D-sub male, RS-232 with handshaking
Consult*	Custom 20 mA/RS-232 serial interface cable

\*Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5 ft. \$2.00 charge for each additional foot.